

NOTES:

1.MATERIAL:

MOLDING: LCP UL94 V-0  
 CONTACT: COPPER ALLOY.  
 GOLD PLATED Min ON CONTACT AREA, 100u"  
 Min TIN (LEAD FREE) ON SOLDER AREA,  
 SHELL: SUS304-H,T=0.30±0.03mm  
 50u" NICKEL PLATING OVER ALL.

2.MECHANICAL:


INSERTION: 5~20N.  
 EXTRACTION: 8~20N AFTER TEST.  
 DURABILITY: 10000 CYCLES

3.ELECTRICAL:



CURRENT: 3A FOR VBUS;  
 1.25A FOR GND PIN.  
 0.25A FOR OTHER.  
 VOLTAGE: 20 V MAX  
 WITHSTANDING VOLTAGE: 100V AC R.M.S.  
 CONTACT RESISTANCE: 40mΩ MAX.  
 INSULATION RESISTANCE: 100MΩ MIN.

4.ENVIRONMENTAL

TEMPERATURE RANGE -25°C ~ +85°C



防水圈图

 <b>深圳市兆达鑫科技有限公司</b> Shenzhen Zhao Xin Technology Co., Ltd.			
TOLERANCE: X.X ±0.30 X.XX ±0.20 X.XXX ±0.10 X.° ±10° X' ±5° X" ±5°	DRAWN BY : <b>刘志强</b>	DATE : <b>2015.08.18</b>	PART NAME: <b>TYPE-C2P防水带螺丝孔焊线式H11.5</b>
	CHECKED BY: <b>李毅</b>	DATE : <b>2015.08.18</b>	PART NO. <b>SEE TABLE</b> MOLD NO. <b>SEE TABLE</b>
UNIT: mm [inch] SCALE: 1:1    SIZE: A4	APPROVED BY: <b>张少辉</b>	DATE : <b>2015.08.18</b>	DRAW NO.: <b>ZDHS0600FS205</b> SHEET NO.: <b>1 OF 1</b>