



RECOMMEND PCB LAYOUT

NOTES:

- Housing: Thermoplastics,UL94V-0
- Contact: Copper Alloy
- Shell: Copper Alloy/Steel
- Voltage Current Rating:1.5 AMP. 30V AC
- Insulation Resistance:1000MΩ Min.
- Contact Resistance:30 MΩ Max.
- Dielectric Withstanding Voltage:500W AC
- Temperature Range: -35°C to +85°C
- Insulator color: Black/White
- Plastic material:PBT/LCP/Others
- Shell finish:Nickel plated/Tin-Lead plated
- Mechanical:
- Mating Force:3.5KG MAX
- Unmating Force:1.02 KG MIN.
- Contact finish:
- 01: Selective Gold Flash
- 02: Selective Gold 3U"
- 03: Selective Gold 5U"
- 04: Selective Gold 15U"
- 05: Selective Gold 30U"

| | | | |
|--|---------------------|----------------------|--|
| 深圳市兆达鑫科技有限公司 Shenzhen Zhao Xin Technology Co., Ltd. | | | |
| TOLERANCE: X.X ±0.30 X.XX ±0.20 X.XXX ±0.10 X.XX ±0.10 X.X ±0.05 X ±0.05 | DRAWN BY : 刘志强 | DATE : 2015.08.18 | PART NAME: 双层直插10.0直边鱼叉脚 |
| UNIT: mm [inch] SCALE:1:1 SIZE: A4 | CHECKED BY: 李毅 | DATE : 2015.08.18 | PART NO. SEE TABLE MOLD NO. |
| | APPROVED BY: 张少辉 | DATE : 2015.08.18 | DRAW NO: ZDXAFUSB20504 SHEET NO. 1 OF 1 |