


NOTE:
 1.Rating:AC125V 5A/250V 3A
 2.Operating froce:100±30gf
 3.Mechanical Life:100,000
 3.Electrical Life:6000-10,000



Circuit Diagram

⑧	Shrapnel 2	—	1	Copper Alloy	—	—
⑦	Shrapnel 1	—	1	Beryllium Copper	—	—
⑥	Contact	—	1	Copper Alloy	Plating silver	—
⑤	Aluminum rivet	—	1	Aluminum Alloy	—	—
④	Terminal	—	3	Copper Alloy	Plating silver	—
③	Housing	—	1	PBT	Black	—
②	Knob	—	1	PBT	Black	—
①	Cover	—	1	PBT	Black	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE		深圳市兆达鑫科技有限公司 Shenzhen Zhao Xin Technology Co., Ltd.		
DRAWN	刘志强	2015.08.18				
CHECKED	李文毅	2015.08.18		TITLE:	MICRO SWITCHS	
APPROVALS	张少辉	2015.08.18		PART NO.	MX-94-3P	
TOLERANCES ARE			30~以下	±0.30	ANGLE	UNIT: mm
			10~20	±0.25		
			5~10	±0.20	SCALE: 1:1	PROJ:
			~ 5	±0.20		

_____	A	_____	NEW	_____	_____	_____
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.