


NOTE:  
 1. Rating: AC125V 5A/250V 3A  
 2. Operating froce: 25±10gf  
 3. Mechanical Life: 1,000,000  
 3. Electrical Life: 6000-10,000



Circuit Diagram

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
⑧	Shrapnel 2	—	1	Copper Alloy	—	—
⑦	Shrapnel 1	—	1	Beryllium Copper	—	—
⑥	Contact	—	1	Copper Alloy	Plating silver	—
⑤	Lever	—	1	Stainless Steel	—	—
④	Terminal	—	3	Copper Alloy	Plating silver	—
③	Housing	—	1	PBT	Black	—
②	Knob	—	1	PBT	Black	—
①	Cover	—	1	PBT	Black	—

APPROVALS		DATE	ZDX 深圳市兆达鑫科技有限公司 Shenzhen Zhao Xin Technology Co., Ltd.		
DRAWN	刘志强	2015.08.18	TITLE:	MICRO SWITCHES	
CHECKED	李文毅	2015.08.18	PART NO.	MX-94-3P-W	
APPROVALS	张少辉	2015.08.18	TOLERANCES ARE	ANGLE	UNIT: mm SCALE: 1:1 PROJ:
			30~以下 ±0.30	±2'	DRAWING NO. SHEET 1 OF 1
			10~20 ±0.25		
			5~10 ±0.20		
			~ 5 ±0.20		

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			