



NOTE:

- 1. Rating: AC125V 5A/250V 3A
- 2. Operating froce: 30±10gf
- 3. Mechanical Life: 1,000,000
- 3. Electrical Life: 6000-10,000

①	Aluminum rivet	—	1	Aluminum Alloy	—	—
⑩	Spindle	—	1	Brass	Plating Nicke	—
⑨	Roller	—	1	Brass	Plating Nicke	—
⑧	Shrapnel 2	—	1	Copper Alloy	—	—
⑦	Shrapnel 1	—	1	Beryllium Copper	—	—
⑥	Contact	—	1	Copper Alloy	Plating silver	—
⑤	Lever	—	1	Stainless Steel	—	—
④	Terminal	—	3	Copper Alloy	Plating silver	—
③	Housing	—	1	PBT	Black	—
②	Knob	—	1	PBT	Black	—
①	Cover	—	1	PBT	Black	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE		ZDX 深圳市兆达鑫科技有限公司 Shenzhen Zhao Xin Technology Co., Ltd.																	
DRAWN	刘志强	2015.08.18		TITLE:	MICRO SWITCHS																
CHECKED	李文毅	2015.08.18		PART NO.	MX-94-L带轮																
APPROVALS	张少辉	2015.08.18		TOLERANCES ARE	<table border="1"> <tr> <td>30~以下</td> <td>±0.30</td> <td rowspan="2">ANGLE</td> <td rowspan="2">UNIT: mm</td> <td rowspan="2">SCALE: 1:1</td> <td rowspan="2">PROJ: </td> </tr> <tr> <td>10~20</td> <td>±0.25</td> </tr> <tr> <td>5~10</td> <td>±0.20</td> <td rowspan="2">±2'</td> <td rowspan="2">DRAWING NO.</td> <td rowspan="2">SHEET 1 OF 1</td> </tr> <tr> <td>~ 5</td> <td>±0.20</td> </tr> </table>		30~以下	±0.30	ANGLE	UNIT: mm	SCALE: 1:1	PROJ:	10~20	±0.25	5~10	±0.20	±2'	DRAWING NO.	SHEET 1 OF 1	~ 5	±0.20
30~以下	±0.30	ANGLE	UNIT: mm	SCALE: 1:1	PROJ:																
10~20	±0.25																				
5~10	±0.20	±2'	DRAWING NO.	SHEET 1 OF 1																	
~ 5	±0.20																				

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
—	A	—	NEW	—	—	—