


CHARACTERISTICS	
OPERATING FORCE(OF):	200gf Max.
RELEASE FORCE(RF):	30gf Min.
OPERATING POSITION:	3.6±0.6 mm.
PRE TRAVEL:	3.5mm Max.
DIFFERENTIAL TRAVEL:	0.6mm Max.
FREE POSITION:	7.1mm Max.


ELECTRICAL DATA	
RATING	OPERATING LIFE
3A 12VDC	100,000 CYCLES
0.1A 48VDC 125/250VAC	100,000 CYCLES
MECHANICAL LIFE	500,000 CYCLES
GAP TYPE	MICRO
OPERATING TEMP	-20℃~+85℃
WATERGROOF	IP67

Circuit Diagram



TOLERANCE UNLESS OTHERWISE SPECIFIED

≡	1~3	3~10	10~30	30~100	100~200	ANGLE
±0.2	±0.3	±0.4	±0.6	±1.0	±1.5	±3.0°



SCALE	UNIT	MM
	VERSION REV	A1

深圳市兆达鑫科技有限公司
Shenzhen Zhao Xin Technology Co., Ltd.

DRAFTED BY	BING WAIG	DATE	2020-6-15
CHECKED BY	GUO FU LUO	DATE	2020-6-15
APPROVED BY	MATH	DATE	2020-6-15

ZDX-HS-001-07