


Circuit Diagram



CHARACTERISTICS

OPERATING FORCE (OF):	130gf Max.
RELEASE FORCE (RF):	15gf Min.
OPERATING POSITION:	3.45±0.2 mm.
PRE TRAVEL:	0.80mm Max.
DIFFERENTIAL TRAVEL:	0.20mm Max.
FREE POSITION:	4.10mm Max.

ELECTRICAL DATA

RATING	OPERATING LIFE
3A 12VDC	100,000 CYCLES
0.1A 48VDC 125/250VAC	100,000 CYCLES

MECHANICAL LIFE	500,000 CYCLES
GAP TYPE	MICRO
OPERATING TEMP	-20℃~+85℃
WATERGROOF	IP67


OUTLINE DRAWING

深圳市兆达鑫科技有限公司
Shenzhen Zhao Xin Technology Co., Ltd.

DRAFTED BY	BING WANG	DATE	2020-6-13
CHECKED BY	GUO FU LUO	DATE	2020-6-13
APPROVED BY	MATH	DATE	2020-6-13

TOLERANCE UNLESS OTHERWISE SPECIFIED

Q	1~3	3~10	10~30	30~100	100~200	ANGLE	
	±0.2	±0.3	±0.4	±0.6	±1.0	±1.5	±3.0°



SCALE	
UNIT	mm
VERSION REV	A1

ZDX-HS-H3-C